# **Roborock S8 Max Ultra** Robotic Vacuum Cleaner User Manual

Read this user manual with diagrams carefully before using this product and store it properly for future reference.



English	04
Français	19
Español	33

## Contents

- 05 Safety Information
- 07 Battery and Charging
- 07 International Symbols Explanation
- 08 FCC/IC Statement
- 09 Product Overview
- 10 Installation
- 11 Connecting to the App
- 11 Instructions for Use
- 13 Routine Maintenance
- 16 Environment Protection Information
- 16 Basic Parameters
- 17 Common Issues

# Safety Information WARNING

- For use only with roborock EWFD13LRR or EWFD14LRR charger.
- To prevent injury caused by blades used to cut hair inside the main brush cover, make sure to install two main brushes in place before installing the main brush cover.
- The product must be switched off and the plug must be removed from socket outlet when not in use, before cleaning or maintaining the product.
- Connect to a properly grounded outlet only. See Grounding Instructions.

# CAUTION

- Only use the product in accordance with the User Manual. Any loss or damage caused by improper use will be borne by the user.
- Make sure dustbin, washable filter, dust bag, side brush, mop cloth, main brushes and main brush cover are installed in place before cleaning.
- Do not sit or stand on the robot or dock.
- To prevent corrosion or damage, do not use any disinfectant and only use cleaning solution recommended by Roborock in the solution cartridge.
- Do not put any low objects (such as shoes, mats) near raised areas like stairs. Otherwise, the robot may fall down caused by malfunctional sensors.
- To prevent water damage, make sure that the floor where the robot operates is free of water.
- Place the cords from other appliances out of the area to be cleaned.
- Do not operate the vacuum in a room where an infant or child is sleeping.
- Do not operate the vacuum in an area where there are lit candles or fragile objects on the floor to be cleaned.
- Do not operate the vacuum in a room that has lit candles on furniture that the vacuum may accidentally hit or bump into.
- Do not allow children to sit on the vacuum.
- Do not carry the robot using vertical bumper, top cover, side brush or bumper. Do not move the dock by lifting the dock base, water tank handles or dust container cover.
- Place the dock on a hard, flat floor away from fire, heat, and water. Avoid narrow spaces or locations where the robot may be suspended in the air.
- This product can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the

product in a safe way and understand the hazards involved. Children shall not play with the product. Cleaning and user maintenance shall not be made by children without supervision.

- Do not dismantle, repair or modify the battery or charging dock.
- If the dock is placed in an area susceptible to thunderstorms or with unstable voltage, take protection measures.
- Do not rinse the robot and the dock.
- $\bullet$   $\triangle$  To avoid burns from hot water, do not touch the water outlets.

# **GROUNDING INSTRUCTIONS**

This appliance must be grounded. If it should malfunction or breakdown, grounding provides a path of least resistance for electric current to reduce the risk of electric shock. This appliance is equipped with a cord having an equipment-grounding conductor and grounding plug.

The plug must be inserted into an appropriate outlet that is properly installed and grounded in accordance with all local codes and ordinances.

WARNING – Improper connection of the equipment-grounding conductor can result in a risk of electric shock. Check with a qualified electrician or service person if you are in doubt as to whether the outlet is properly grounded. Do not modify the plug provided with the appliance – if it will not fit the outlet, have a proper outlet installed by a gualified electrician.

This appliance is for use on a nominal 120-V circuit and has a grounding attachment plug that looks like the plug illustrated in sketch A in Grounding methods. Make sure that the appliance is connected to an outlet having the same configuration as the plug.

No adaptor should be used with this appliance.

### **Grounding methods**



# **Battery and Charging**

- Keep the charging dock away from heat (such as radiators).
- Do not wipe the charging contacts with wet cloth or wet hands.
- Before placing the robot into storage, charge it fully, turn it off, and then choose a cool, dry place. Recharge it at least every three months to avoid battery overdischarge.
- Do not use the product when the temperature is higher than 40°C (104°F) or lower than 4°C (39°F), or there is any liquid or sticky substance on the floor.
- Do not discard waste batteries. Leave them with a professional recycling organization.
- To transport the product, make sure it is powered off and shut down, and empty the remaining fluid in the water tanks. At the same time, empty and rinse the cleaning solution cartridge, leave it air dry completely and then reinstall it. Original packaging is advised.

# **International Symbols Explanation**

- ~ ALTERNATING CURRENT symbol [symbol IEC 60417-5032 (2009-02)]
- ) PROTECTIVE EARTH (Protective Ground) symbol [symbol IEC 60417-5019 (2009-02)]

# **FCC/IC Statement**

Compliance Information			
Product Name	Robotic Vacuum Cleaner with Charging Dock		
Product Model	Robotic Vacuum Cleaner Model: S83USC Empty Wash Fill Dock: EWFD13LRR Empty Wash Fill Dock Auto: EWFD14LRR		
Compliance Statement	<ul> <li>This device complies with Part 15 of the FCC Rules.</li> <li>Operation is subject to the following two conditions: <ul> <li>(1) this device may not cause harmful interference, and</li> <li>(2) this device must accept any interference received, including interference that may cause undesired operation.</li> <li>This device contains licence-exempt transmitter(s)/receiver(s) that comply with</li> <li>Innovation, Science and Economic Development Canada's licence-exempt RSS(s).</li> <li>Operation is subject to the following two conditions:</li> <li>(1) This device may not cause interference.</li> <li>(2) This device must accept any interference, including interference that may cause undesired operation of the device.</li> </ul> </li> </ul>		
Correspondence of the responsible party in USA			
Company	Roborock Technology Co.		
Address	ROOM 1227, 12TH FLOOR, 1000 N. WEST STREET, WILMINGTON, DE 19801		
Email	support@roborock.com		

# A Product Overview

# All Robot (Top View)



### -Mop Only/Child Lock

- Press to start Mop Only
- Press and hold for 3 seconds to enable/disable Child Lock

### Power/Clean

- Press and hold to turn the robot on or off
- Press to start cleaning

### –Power Indicator Light

- White: Battery level  $\geq 15\%$
- Red: Battery level < 15%
- Breathing: Charging or starting up
- Flashing red: Error

### —Dock

- Press to start docking/emptying
- Press and hold to wash the mop cloths

**Note:** Press any button to pause the robot during cleaning or docking.

### A1-1—Vertical Bumper

- A1-2—LiDAR Sensor
- A1-3—Wall Sensor
- A1-4—Reactive 3D Obstacle Avoidance Sensor
- A1-5—Dock Locator
- A1-6—Infrared Fill Light

## Robot (Bottom View)

- A2-1—Cliff Sensors
- A2-2—Carpet Sensor
- A2-3—Omnidirectional Wheel
- A2-4—Flexible Side Brush
- A2-5—Main Brushes
- A2-6—Main Brush Cover Latches
- A2-7—Main Wheels

## A3 Robot (Top Cover Open)

### A3-1—WiFi Indicator Light

- Off: WiFi disabled
- Flashing slowly: Waiting for connection
- Flashing quickly: Connecting
- Steady: WiFi connected
- A3-2—Reset Button
- A3-3—Charging Contacts
- A3-4—Communication Sensor
- A3-5—Self-Filling Port
- A3-6—Positioning Button
- A3-7—Air Outlets
- A3-8—VibraRise Module
- A3-9—Bumper

## 🛯 VibraRise Module

A4-1—Mop Cloth Attachment Slot A4-2—Vibration Module

A4-3—Edgewise Mopping Module

Note: The mop cloth mounts are non-detachable.

## A5 VibraRise Mop Cloth

### A5-1—Hook and Loop Pads

Note: Secure the mop cloth flat in place.

# **A6** Edgewise Mop Cloth

A6-1—Mop Cloth Screw

### A Dustbin

A7-1—Dustbin Latch A7-2—Filter Latch A7-3—Air Inlet A7-4—Washable Filter A7-5—Suction Inlet

## AB Dock Base

A9 Disposable Dust Bag

**Dower Cord** 

### 💷 Empty Wash Fill Dock

A11-1—Water Tank Handle A11-2—Water Tank Lid A11-3—Water Tank Latch A11-4—Clean Water Tank A11-5—Drying Air Outlets A11-6—Cleaning Tank of Edgewise Mopping Module

- A11-7—Dock Base A11-8—Charging Contacts
- A11-9—Robot Refill Port
- A11-10—Dirty Water Tank

### A11-11—Status Indicator Light

- Breathing: Emptying/Mop washing
- Red: Dock error
- Dim: Charging/Drying
- Off: Powered off

**Note:** To minimize disturbance, the indicator light will be off or dim in Do Not Disturb (DND) mode.

#### A11-12—Dust Container Cover

- A11-13—Mop Washing Module
- A11-13-1—High-Speed Maintenance Brush
- A11-13-2—Washing Strip
- A11-13-3—Water Outlets
- A11-13-4—Maintenance Brush Latch
- A11-14—Cleaning Solution Cartridge
- A11-15—Dust Bag Slot
- A11-16—Filter
- A11-17—Dock Location Beacon
- A11-18—Suction Inlet
- A11-19—Water Filter

# Power Cord Storage

A12-1—Cord Storage Slot A12-2—Power Port A12-3—Cord Outlets

Note: Power cord can exit at either side.

# Installation

## **BD** Important Information

- B1-1—Tidy cords, hard or sharp objects (such as nails and glass), and loose items from the ground and move any unstable, fragile, precious, or dangerous items to prevent personal injury or property damage due to items becoming tangled in, struck by, or knocked over by the robot.
- B1-2—When using the robot in a raised area, always use a physical security barrier to prevent accidental falls that may result in personal injury or property damage.

#### Notes:

- When using the robot for the first time, follow it throughout its whole cleaning route and watch for potential problems. The robot will be able to clean by itself in future uses.
- To prevent excessive buildup of dirt on the mop cloths, floors should be vacuumed at least three times before the first mopping cycle.

# B Positioning the Dock

- B2-1— Place the dock on a hard, flat floor (wood/tile/concrete etc.), flat against a wall, and remove the foam used to secure the mop washing module in shipment at the bottom.
- B2-2—Attach the dock base by pressing down both sides of the base firmly, and then pressing the connecting part

in the middle until you hear a click.

- B2-3— Connect the power cord to the back of the dock, and keep the excess cord inside the storage slot.
- B2-4— Reserve a space of at least 0.82 m (2.7 ft) in height, 0.42 m (1.4 ft) in width and 1 m (3.3 ft) in depth. Make sure that the location has good WiFi access for a better experience with the mobile app. Plug in and make sure that the status indicator light is on.

### B2-4-1—More than 0.82 m (2.7 ft) B2-4-2—More than 1 m (3.3 ft) B2-4-3—More than 0.42 m (1.4 ft)

#### Notes:

- If the power cord hangs vertically to the ground, it may be caught by the robot, causing the dock to be moved or disconnected.
- The status indicator light is bright when the dock is powered on, and dim during robot charging or mop cloth drying.
- The status indicator light turns red if an error occurs.
- Place the dock on a hard, flat floor away from fire, heat, and water. Avoid narrow spaces or locations where the robot may be suspended in the air.
- Placing the dock on a soft surface (carpet/mat) may cause the dock to tilt and cause docking and departing problems.
- Keep the dock away from direct sunlight or anything that may block the dock location beacon, otherwise the robot may fail to return to the dock.
- Do not use the dock without the clean water tank, dirty water tank, high-speed maintenance brush, dust container cover, disposable dust bag, cleaning tank of edgewise mopping module, cleaning solution cartridge, or water filter.
- Maintain the dock according to the Routine Maintenance. Do not clean the dock power cord and charging contacts with a wet cloth or tissue.

 All docks are subject to water-based tests before leaving the factory. It is normal that a small amount of water remains in the waterway of the dock.

### Powering On & Charging

Press and hold () to power on the robot. Wait until the power indicator light is steady, and then place the robot in front of the dock. Make sure that the dock is plugged in. Then, press and the robot will automatically return to the dock for charging. The robot is equipped with a built-in high-performance lithium-ion rechargeable battery pack. To maintain battery performance, keep the robot charged.

B3-1— Dock status indicator light dim, robot power indicator light breathing: Charging

**Note:** The robot may not be turned on when the battery is low. In this case, place the robot to the dock for charging.

# **Connecting to the App**

## 1. Download the App

Search for "Roborock" in the App Store or Google Play or scan the QR code to download and install the app.



## 2. Reset WiFi

- a. Open the top cover and find the WiFi indicator light.
- b. Press and hold Q and ∩ simultaneously until you hear the "Resetting WiFi" voice message. The reset is complete when the WiFi indicator light flashes slowly. The robot will then wait for a connection.

Note: If you cannot connect to the robot due to your router configuration, a forgotten password, or any other reason, reset the WiFi and add your robot as a new device.

### 3. Add Device

Open the Roborock app, tap the "Scan to Connect" or "Search for Device" button and add your device following the in-app guide.

#### Notes:

- The actual process may vary due to ongoing app updates. Follow the guide provided in the app.
- Only 2.4 GHz WiFi is supported.
- If the robot waits more than 30 minutes for a connection, WiFi will be automatically disabled. If you want to reconnect, reset the WiFi before proceeding.

# **G** Instructions for Use

## Filling the Clean Water Tank

Lift the clean water tank, open its top cover, and then fill it with tap water. After filling, close the cover and put the clean water tank back to the dock.

#### Notes:

- To avoid deformation, only use cold water.
- If any water stains remain on the outside of the water

tank, wipe them with a soft, dry cloth before reinstalling the tank.

- To prevent a high concentration of cleaning solution, add solution only to the cleaning solution cartridge.
- The lid of clean water tank is non-detachable.

### 🕑 Adding the Cleaning Solution

C2-1— Remove the dust container cover, pull out the entire cleaning solution cartridge by its bottom handle, and then place it on a hard, flat surface.

**Note:** To prevent the dust container cover from falling and hitting the robot, remove the cover with both hands, one on each side.

- **C2-2** Open the lid of the cartridge and add cleaning solution.
- C2-3— Close the lid and put the cartridge back to the dock. Press down the cartridge until you hear it lock with a click.
- C2-4—Install the dust container cover in place to make sure the dust container is securely sealed.

#### Notes:

- Make sure that the cleaning solution cartridge is entirely removed before adding cleaning solution.
- To prevent corrosion or damage, do not use any disinfectant and only use cleaning solution recommended by Roborock in the solution cartridge.
- Cleaning solution is not included in the package.
   Purchase one if needed.

## Control Con

Press and hold  $\bigcirc$  to turn on the robot. The power indicator light will come on, and the robot will be on standby.

Press and hold () to turn off the robot and complete the cleaning cycle.

Note: The robot cannot be turned off when it is being charged.

### **C** Starting Cleaning

Press () to start cleaning. The robot will plan its cleaning route and in each room, it firstly draws out zone edges and then fills the room in a zigzag pattern. In so doing, the robot cleans all rooms one by one, thoroughly and efficiently.

Zone 1 – Cleaned Zone 2 – Cleaned



Zone 4 – Next Zone Zone 3 – In Progress

#### Notes:

- To make sure the robot returns to the dock automatically, start the robot from the dock and do not move the dock during cleaning.
- Cleaning cannot start if the battery level is too low. Allow the robot to charge before starting a cleanup.
- If cleaning is completed in less than 10 minutes, the robot will clean the area twice.
- If the battery runs low during a cleaning cycle, the robot will automatically return to the dock. After charging, the robot will resume where it left off.
- The robot will retract the mop cloth mounts to clean the carpet. You can also set the carpet as a no-go zone in the app to avoid it.
- Before starting each cleaning task, make sure that the mop cloths have been properly installed.

# G Spot Cleaning

Press  ${\bf Q}$  and  ${\bf \bigcup}$  simultaneously to start spot cleaning.

Cleaning range: The robot cleans a 1.5 m (4.9 ft)  $\times$  1.5 m (4.9 ft) square area centered on itself.

**Note:** After spot cleaning, the robot will automatically return to the starting point and be on standby.

# C Mop Only

Press () to start Mop Only. The main brushes rise, the main brushes and fan stop operating, and the VibraRise module lowers.

**Note:** Compared with the traditional cleaning mode, noise emanating from Mop Only is much lower.

### Pause

When the robot is running, press any button to pause it, press () to resume cleaning, press () to send it back to the dock, and press and hold () to wash the mop cloths and then resume cleaning.

**Note:** Placing a paused robot on the dock manually will end the current cleanup.

# CB Sleep

If the robot is paused for over 10 minutes, it will go to sleep, and the power indicator light will flash every few seconds. Press any button to wake the robot up.

#### Notes:

• The robot will not go to sleep when it is charging.

• The robot will automatically shut down if left sleep for more than 12 hours.

## 🐵 Washing the Mop Cloths

During cleaning, the robot automatically determines when it should return to the dock for mop washing and water tank refilling to maximize its mopping performance. To manually start washing, press and hold  $\bigcirc$  or tap the corresponding button in the app. Press any button to stop washing.

#### Notes:

- To make sure the robot to wash the mop cloths automatically, start the robot from the dock and do not move the dock during cleaning.
- Mop wash frequency and mode can be modified in the app.
- To avoid burns from hot water, do not touch the water outlets.

### 💷 Emptying

After cleaning, the robot will return to the dock and auto-emptying will begin as needed. To manually start emptying, press ○ on the docked robot or tap the corresponding button in the app. Press any button to stop emptying.

#### Notes:

- When emptying has been left unused for a long period, empty the dustbin manually and make sure the air inlet is clear for optimal emptying performance.
- Auto-emptying can be disabled in the app.
- · Avoid frequent manual emptying.

## Orying

Drying starts automatically after mop washing or after cleaning is completed. To manually start or stop drying, tap the corresponding button in the app.

#### Notes:

- . Stay away from the drying air outlets during drying.
- Drying duration can be modified in the app.
- Auto-drying can be disabled in the app.

### Auto Cleaning Solution Addition

The robot will automatically add cleaning solution to the water for mop washing and robot water tank refilling according to the preset ratio to ensure optimal mopping performance.

Note: Smart Cleaning Solution Filling can be disabled in the app.

## Charging

After cleaning, the robot will automatically return to the dock to charge. Press ∩ to send the paused robot back to the dock. The power indicator light will breathe during robot charging.

**Note:** If the robot fails to find the dock, it will automatically return to its starting position. Place the robot on the dock manually to recharge.

### OND Mode

The default Do Not Disturb (DND) period is from 22:00 to 08:00. You can use the app to disable the DND mode or modify the DND

period, or set whether to enable auto topup, emptying and drying, to dim the button light, or lower the volume of the voice message during the DND period.

### Child Lock

Press and hold c to enable/disable Child Lock. You can also set it in the app. Once enabled, the robot will not react to button presses when it is stationary. When the robot is cleaning or docking, press any button to pause it.

### CII6 Error

If an error occurs, the power indicator light on the robot will flash red or status indicator light on the dock will be steady red. A popup notification will appear in the app and a voice alert may sound.

#### Notes:

- The robot will go to sleep automatically if left in a malfunctioning state for over 10 minutes.
- Placing a malfunctioning robot on the dock manually will end the current cleanup.

## Resetting the System

If the robot does not respond when a button is pressed or cannot be turned off, reset the system by pressing the Reset button.

**Note:** After resetting the system, existing settings such as scheduled cleaning and WiFi will be restored to factory settings.

### Restoring Factory Settings

If the robot does not function properly after a system reset, switch it on. Press and hold and at the same time, press the Reset button until you hear the "Restoring factory settings" voice message. The robot will then be restored to factory settings.

# D Routine Maintenance

**Note:** The frequency of replacement may vary with the actual situation. If abnormal wear occurs, replace the parts immediately.

### 🕕 Main Brushes

\* Clean every 2 weeks and replace every 6-12 months.

- D1-1—Hair-Blocking Rings
- D1-2—Main Brush Caps
- D1-3—Main Brush Cover
- D1-4—Latches
- D1-5—Main Brushes
- D1-6—Main Brush Bearing
- D1-7—Turn over the robot and press the two latches inwards to remove the main brush cover.
- D1-8—Pull out the main brushes and remove the main brush bearings, main brush caps, and hair-blocking rings. Remove any entangled hair or dirt at both ends of the main brushes. Then, reinstall the hairblocking rings, main brush caps, and main brush bearings.

- D1-9— Reinstall the main brushes. Firmly snap the main brush bearings into place. Only after the bearings are securely installed, fit the main brush cover.
- D1-10—Reinstall the main brush cover. Make sure its four teeth are fully seated in the slots, and press the main brush cover until you hear it lock with a click.

#### Notes:

- It is recommended to wipe the main brushes with a wet cloth. If the main brushes are wet, air-dry them away from direct sunlight.
- Do not use corrosive cleaning fluid or disinfectant to clean the main brushes.
- To prevent injury caused by blades used to cut hair inside the main brush cover, make sure to install two main brushes in place before installing the main brush cover.

### 102 Flexible Side Brush

\* Clean monthly and replace every 3-6 months.

Unscrew the side brush screw. Remove and clean the side brush. Reinstall the brush and tighten the screw.

## Omnidirectional Wheel

\* Clean as required.

D3-1— Use a tool, such as a small screwdriver, to pry out the axle and take out the wheel.

Note: The omnidirectional wheel bracket cannot be removed.

D3-2— Rinse the wheel and the axle with water to remove any hair and dirt. Air-dry, reinstall, and press the wheel and axle back in place. 0 Main Wheels

\* Clean as required.

Clean the main wheels with a soft, dry cloth.

### 05 Dustbin

\* Clean as required.

- D5-1—Open the top cover and press the dustbin latch to take out the dustbin.
- D5-2—Remove the washable filter and empty the dustbin.
- D5-3—Fill the dustbin with clean water and reinstall the washable filter. Gently shake the dustbin, and then pour out the dirty water.

Note: To prevent blockage, only use clean water without any cleaning liquid.

D5-4—Leave the dustbin and the washable filter to dry.

### D Washable Filter

- \* Clean every 2 weeks and replace every 6-12 months.
- D6-1—Remove the filter.
- **D6-2**—Rinse the filter repeatedly and tap it to remove as much dirt as possible.

**Note:** Do not touch the surface of the filter with hands, brush, or hard objects to avoid potential damage.

D6-3—Allow at least 24 hours for the filter to dry thoroughly and reinstall it.

Note: Purchase an additional filter and alternate if necessary.

### D Edgewise Mop Cloth

\* Clean as required and replace every 3-6 months.

- D7-1—Unscrew the screw in the middle of the mop cloth.
- D7-2—Wash the mop cloth and air-dry it.
- D7-3—Reinstall the mop cloth and tighten the screw.

**Note:** A dirty mop cloth will affect the mopping performance. Clean it before use.

### VibraRise Mop Cloth

\* Clean as required and replace every 3-6 months.

D8-1—Remove the mop cloth from the mop cloth mount. Clean the mop cloth and air-dry it.

**Note:** A dirty mop cloth will affect the mopping performance. Clean it before use.

D8-2—Slide the mop cloth in from the opening of the attachment slot, and then stick it flat in place.

### D Robot Sensors

\* Clean as required.

Use a soft, dry cloth to wipe and clean all sensors, including:

- D9-1—Reactive 3D Obstacle Avoidance Sensor
- D9-2—Dock Locator
- D9-3—Carpet Sensor
- D9-4—Wall Sensor
- D9-5—Communication Sensor
- D9-6—Cliff Sensors

# Ontacts

\* Clean as required.

Use a soft, dry cloth to wipe the charging contacts on the robot and the dock.

### **OD** Moving the Dock

To move the dock, grip the cord storage slot on the back with one hand and the inner side of the front board with the other hand. Do not lift the base directly to prevent the dock from falling off.

# Dirty Water Tank

Open the dirty water tank lid and pour out the dirty water. Fill the tank with clean water, close the lid, lock it, and shake. Pour out the dirty water. Lock the lid and reinstall the tank.

#### Notes:

- To avoid deformation, only use cold water.
- If any water stains remain on the outside of the water tank, wipe them with a soft, dry cloth before reinstalling the tank.
- . The lid of dirty water tank is non-detachable.

### 013 High-Speed Maintenance Brush

\* Clean as required and replace every 6-12 months.

Lift the high-speed maintenance brush latch and remove the brush. Remove any entangled objects in the high-speed maintenance brush and rinse it clean. Reinstall the brush and latch it in place.

# • Clean as required.

Pull out the filter. Press the latch on the side of the filter to flip it downwards open. Rinse it with water, use a soft, dry cloth to wipe the cleaning tank, and then reinstall the filter by locking the latch. Press down the filter until you hear it lock with a click.

### OB Cleaning Tank of Edgewise Mopping Module

\* Clean as required.

- D15-1—Remove the cleaning tank.
- D15-2—Rinse the cleaning tank with water.
- D15-3—Reinstall the cleaning tank.

# Replacing the Disposable Dust Bag

\* Replace regularly or when it is full.

D16-1—Remove the dust container cover.

**Note:** To prevent the dust container cover from falling and hitting the robot, remove the cover with both hands, one on each side.

D16-2—Remove the dust bag and discard it.

#### Notes:

- The dust bag handle seals the bag on removal to prevent leakage.
- Always install a dust bag before putting back the dust container cover to avoid auto-emptying without the bag. You can also disable auto-emptying in the app.

#### D16-3—Clean the filter with a dry cloth, insert a new disposable dust bag into the slot, and spread it evenly to

Note: Make sure the disposable dust bag is properly installed to avoid waste escaping and damaging the dock.

D16-4—Install the dust container cover in place to make sure the dust container is securely sealed.

### 000 Battery

The robot is equipped with a built-in highperformance lithium-ion rechargeable battery pack. To maintain battery performance, keep the robot charged during normal use.

**Note:** If the robot will be left unused for a long period, turn it off and charge it at least every three months to avoid battery damage caused by overdischarge.

# Environment Protection Information

### **Removing the Battery**

\* The following information applies only when disposing of the robot and should not be followed for day-to-day operations.

The chemical substances contained in the built-in lithium-ion battery of this product can cause environmental pollution. Remove the battery before disposing of this product and hand it to a professional battery recycling facility for centralized disposal.

- 1. Operate the robot without connecting to the dock until it runs out of battery.
- 2. Turn off the robot.
- 3. Unscrew the battery cover.
- 4. Remove the battery cover.
- 5. Press the latch to pull out the battery connector and remove the battery.

#### Notes:

- Before removing the battery, make sure it is fully drained. Do not attempt to remove the battery if the robot is connected to the dock.
- Remove the entire battery pack. Avoid damaging the battery pack casing to avoid short-circuits or leakage of hazardous substances.
- In the event of accidental contact with battery fluid, rinse thoroughly with water and seek immediate medical care.

# **Basic Parameters**

### Robot

Model	S83USC
Battery	14.4V/5200mAh (TYP) lithium-ion battery
Rated Input	20V 1.5A
Charging Time	Approx. 4 hours

Note: The serial number is on a sticker on the underside of the robot.

### **Empty Wash Fill Dock**

EWFD13LRR	
120V~	
60Hz	
6A	
12A	
1.35A	
20V <del></del> 1.5A	
14.4V/5200mAh (TYP) lithium-ion battery	

# **Common Issues**

Issue	Solution	Issue	Solution
Unable to power on	<ul> <li>Battery low. Put the robot on the dock and charge it before use.</li> <li>Battery temperature too low or too high. Only use the robot within the range of 4-40°C (39-104°F).</li> </ul>	Is power always being drawn when the robot is on the dock?	<ul> <li>The robot will draw power while it is docked to maintain battery performance, but the power consumption is extremely low.</li> </ul>
Unable to charge	<ul> <li>Dock not connected to power. Check whether both ends of the power cord are properly connected.</li> <li>Poor contact. Clean the charging contacts of the dock and the robot.</li> <li>Confirm that the dock indicator light is on.</li> </ul>	Does the robot need to be charged for at least 16 hours for the first three	<ul> <li>No. Lithium-ion batteries have no memory effect. The robot can be used once fully charged.</li> </ul>
Slow charging	<ul> <li>When used at high or low temperatures, the robot will automatically reduce its charging speed to extend battery life.</li> <li>Charging contacts dirty. Wipe them with a dry cloth.</li> </ul>	uses? The robot does not resume cleaning after recharging	<ul> <li>Make sure that the robot is not in DND mode. DND mode will prevent auto top-up.</li> <li>If the robot is placed manually on the dock or sent to dock by pressing buttons, it will not be able to resume cleaning.</li> </ul>
Unable to return to dock	• Too many obstacles near the dock. Move it to an open area.		
Noice during	<ul> <li>Robot too far from the dock. Place it closer and retry.</li> <li>The main brushes, flexible side brush, or main wheels may be jammed. Turn off the robot and clean them.</li> </ul>	Scheduled cleaning is not working	• Keep the robot charged. Scheduled cleaning can only begin when the battery level is above 15%.
cleaning • The omnidire	<ul> <li>The omnidirectional wheel may be jammed. Use a screwdriver to remove it for cleaning.</li> </ul>	The flexible side	• Check whether the FlexiArm Extend Cleaning feature is enabled in the app.
• Unable to connect to WiFi	<ul> <li>WiFi disabled. Reset the WiFi and try again.</li> <li>Poor WiFi signal. Move the robot to an area with good WiFi reception.</li> <li>Abnormal WiFi connection. Reset the WiFi, download the latest app version and retry.</li> <li>Unable to connect to WiFi abruptly. There may be an error with your router settings. Contact Roborock Customer Service for help with troubleshooting.</li> </ul>	brush is unable to extend	<ul> <li>The flexible side brush does not extend for every corner or every time when the robot cleans along the wall.</li> <li>Check whether the flexible side brush is jammed.</li> </ul>
		The edgewise mopping module is unable to rotate	• Check whether the edgewise mopping module is jammed.

# **Common Issues**

Solution	Issue	Solution
• The wall sensor, cliff sensors, or carpet sensor may be dirty. Clean them with a soft, dry cloth.	Reduced mop washing performance	<ul> <li>The mop cloths are not attached properly. Reinstall them.</li> <li>The floor is dirty. Change the mop washing mode to "Deep" in the app for better cleaning.</li> </ul>
<ul><li>The dustbin is full and needs emptying.</li><li>The filter is blocked and needs cleaning.</li><li>The main brushes are tangled up. Clean the main brushes.</li></ul>	Unable to auto-empty	<ul> <li>Auto-emptying is disabled. Check in-app settings.</li> <li>Dock dust container cover is not installed. Check and install.</li> <li>Auto-emptying will not be triggered if the robot returns to the dock without cleaning.</li> <li>The robot will not auto-empty after returning to the dock in DND mode. Adjust cleaning or DND period, or start emptying manually.</li> </ul>
Use the mobile app to increase the scrub intensity & water flow.		
<ul> <li>The dust container cover is not in place. Check and install in place.</li> <li>Voltage error. Check that the local voltage meets the requirements listed on the dock.</li> <li>Check clean water tank placement or refill the tank as required.</li> <li>Check dirty water tank placement or empty the tank as required.</li> <li>Check that the water filter has been correctly installed.</li> </ul>		
	Unable to wash the mop cloths	<ul> <li>The mop cloths will not be washed if not used.</li> <li>If the robot does not start from the dock or no dock is found on the app map, it will not return to the dock for mop washing.</li> <li>Check tank placement and refill or empty the tank as required.</li> <li>Check that the water filter has been correctly installed.</li> </ul>
<ul> <li>The main brushes or main brush cover is not properly installed. Check and install in place.</li> <li>The filter, suction inlet, air inlet, or dustbin is blocked. Clean to remove blockage.</li> </ul>	Unable to start auto-drying	<ul> <li>Auto-drying is disabled. Check in-app settings.</li> <li>If you press a robot button or the robot departs the dock during drying, the drying will end in advance.</li> <li>In a humid environment, it is recommended to extend the drying duration in the app to improve the drying</li> </ul>
<ul> <li>If the brush module stops at the left side, it may be jammed. Remove any items jamming it.</li> <li>If the brush module stops at the right side, the filter mouse blocked or is ost installed in place. Clean and</li> </ul>	Unable to wash the mop cloths with hot water	<ul> <li>Performance.</li> <li>Check that Mop Washing with Hot Water is enabled in the app.</li> </ul>
	<ul> <li>The wall sensor, cliff sensors, or carpet sensor may be dirty. Clean them with a soft, dry cloth.</li> <li>The dustbin is full and needs emptying.</li> <li>The filter is blocked and needs cleaning.</li> <li>The main brushes are tangled up. Clean the main brushes.</li> <li>Use the mobile app to increase the scrub intensity &amp; water flow.</li> <li>The dust container cover is not in place. Check and install in place.</li> <li>Voltage error. Check that the local voltage meets the requirements listed on the dock.</li> <li>Check clean water tank placement or refill the tank as required.</li> <li>Check dirty water tank placement or empty the tank as required.</li> <li>Check that the water filter has been correctly installed.</li> <li>The main brushes or main brush cover is not properly installed. Check and install in place.</li> <li>The filter, suction inlet, air inlet, or dustbin is blocked. Clean to remove blockage.</li> <li>If the brush module stops at the left side, it may be jammed. Remove any items jamming it.</li> </ul>	<ul> <li>The wall sensor, cliff sensors, or carpet sensor may be dirty. Clean them with a soft, dry cloth.</li> <li>The dustbin is full and needs emptying.</li> <li>The filter is blocked and needs cleaning.</li> <li>The main brushes are tangled up. Clean the main brushes.</li> <li>Use the mobile app to increase the scrub intensity &amp; water flow.</li> <li>The dust container cover is not in place. Check and install in place.</li> <li>Voltage error. Check that the local voltage meets the requirements listed on the dock.</li> <li>Check clean water tank placement or refill the tank as required.</li> <li>Check dirty water tank placement or empty the tank as required.</li> <li>Check that the water filter has been correctly installed.</li> <li>The main brushes or main brush cover is not properly installed. Check and install in place.</li> <li>If the brush module stops at the left side, it may be jammed. Remove any items jamming it.</li> <li>If the brush module stops at the right side, the filter</li> </ul>